

GROSSING STATION



Application

Pathological sampling bench is widely used in hospital pathology department, pathology laboratories, etc. Reasonable ventilation system protects operator away from harmful gases produce by the formalin during sampling. The hot & cold water system ensures it can adapt to different working climates.

Advantages

1. Odor-removal function.
2. Single water sink, two-person operations.
3. Exhaust air system; High power suction device, low noise operation.
4. Optional water heater is available, hot & cold adjustment.
5. The base cabinet is inward coved type, convenient for sitting operation.
6. Optional pulverizer can completely pulverize waste during test, to avoid blocking drainage pipes.
7. Automatic flushing device, slightly right side incline work table, easy for waste discharge and cleaning.

Technical Specifications

Model		QCT-1000	QCT-1500	QCT-1800
Nominal Size (mm / ft)		1000mm / 3.5ft	1500mm / 5ft	1800mm/ 6ft
External Size (W x D x H) (mm)		1000 x 750 x 1950	1500 x 750 x 1950	1800 x 750 x 1950
Internal Work Area (W x D x H) (mm)		895 x 430 x 900	1395 x 430 x 900	1695 x 430 x 900
Work Surface Height		900mm		
Power Consumption		250W	300W	300W
Optional Water Heater		1500W		
Power Supply		AC 220V ± 10%, 50/60Hz; 110V ± 10%, 60Hz		
Exhaust Airflow Volume		500 – 600 cmh		
Material Construction	Main Body	SS 304 stainless steel		
	Work Table	SS 304 stainless steel		
Standard Accessories		Spotlight, UV Lamp, Fluorescent Lamp, Exhaust system, 4m exhaust duct, Pipe strap		
		Auto flushing device, stainless steel hanger, Adjustable hot & cold water tap		
		180mm deep stainless steel sink, Funnel with filter, Activated carbon filter		
Optional Accessories		Pulverizer, Electrical water heater, Automatic induction hand dryer, eye washer, Camera, Flex magnifier light, Laptop bracket		
Packing Size (W x D x H) (mm)		1160 x 890 x 2170	1660 x 890 x 2170	1960 x 890 x 2170
Gross Weight (kg)		250 kg	300 kg	340 kg